

STANDARD DESIGN WITH THE BLOWER COIL HOUSING PRE-PAINTED METAL IN OUR STANDARD DESERT SAND COLOR.

NOTE (1): A TIME DELAY RELAY (TDR) IS STANDARD IN ALL UNITS.

NOTE (2): IF A TXV IS SHOWN AS REQUIRED, IT IS INCLUDED IN THE PRICE AS FACTORY INSTALLED.

MORTEX STANDARD MULTI-POSITION BLOWER COILS

AIRE-FLO HEAT PUMP	LENNOX MODEL NUMBER	SEER	COOLING CAPACITY CAP. @47	HEATING CAP. @47	HSPF Bluh/Watt	HEATING KW	CIRCUIT BREAKER	STD. PISTON IN COIL	PISTON/TXV KIT REQUIRED
AFHEAT10B24	AMPBC24-10	10.0	24.0	22.8	6.80	10.0	YES	59	59
AFHEAT10B30	AMPBC28-10	10.0	30.0	29.0	6.80	10.0	YES	63	63
AFHEAT10B36	AMPBC29-15	10.0	30.0	29.0	6.80	16.0	YES	63	63
AFHEAT10B36	AMPBC37-10	10.0	34.0	34.4	6.80	10.0	YES	71	71
AFHEAT10B36	AMPBC37-15	10.0	34.0	34.4	6.80	15.0	YES	71	71
AFHEAT10B42	AMPBC42-15	10.0	40.5	40.5	6.80	15.0	YES	76	76
AFHEAT10B42	AMPBC42-20	10.0	40.5	40.5	6.80	20.0	YES	76	76
AFHEAT10B48	AMPBC48-20	10.0	45.5	47.0	7.00	20.0	YES	82	82
AFHEAT10B60	AMPBC60-20	10.0	57.5	58.5	7.00	20.0	YES	90	90

** = 10.0 SEER UNITS REQUIRE A PISTON CHANGE TO MATCH OUTDOOR UNIT TONNAGE AND 11.0 SEER AND ABOVE UNITS

ALL REQUIRE A PISTON CHANGE PER PISTON CHART (OR SEE REQUIRED PISTON ABOVE) IF NO TXV KIT IS SHOWN AS REQUIRED.

MORTEX MULTI-POSITION--EMBOSSED CASED COILS

AIRE-FLO OUTDOOR MODEL	LENNOX MODEL NUMBER	SEER	COOLING CAPACITY CAP. @47	HEATING CAP. @47	HSPF Bluh/Watt	HEATING KW	Width	STD. PISTON IN COIL	PISTON/TXV KIT REQUIRED
AFAIR10B24-A	AFMP24-14.0	10.0	24.0	N/A	N/A	N/A	14.0"	49	49
AFAIR10B24-A	AFMP24-17.5	10.0	24.0	N/A	N/A	N/A	17.5"	49	49
AFAIR10B30-A	AFMP30-14.0	10.0	29.4	N/A	N/A	N/A	14.0"	49	49
AFAIR10B30-A	AFMP30-17.5	10.0	29.4	N/A	N/A	N/A	17.5"	49	49
AFAIR10B36-A	AFMP36-14.0	10.0	35.0	N/A	N/A	N/A	14.0"	59	59
AFAIR10B36-A	AFMP36-17.5	10.0	35.0	N/A	N/A	N/A	17.5"	59	59
AFAIR10B42	AFMP42-17.5	10.0	39.5	N/A	N/A	N/A	17.5"	59	59
AFAIR10B42	AFMP42-20.5	10.0	39.5	N/A	N/A	N/A	20.5"	59	59
AFAIR10B48	AFMP48-17.5	10.0	44.0	N/A	N/A	N/A	17.5"	59	59
AFAIR10B48	AFMP48-20.5	10.0	44.0	N/A	N/A	N/A	20.5"	59	59
AFAIR10B60	AFMP61-20.5	10.0	56.5	N/A	N/A	N/A	20.5"	63	63

HORIZONTAL "SLAB" (DUCT) EMBOSSED CASED COILS

AIRE-FLO OUTDOOR UNIT	SUMMIT HORIZONTAL SLAB EMBOSSED CASED COIL MODEL NUMBER	LENNOX MODEL NUMBER	LENNOX CAT. NUMBER	LENNOX SEER	COOLING CAPACITY	HEATING CAP @47	HSPF	OPENING HEIGHT	OPENING WIDTH	PISTON IN COIL	PISTON / TXV KIT REQUIRED
AFAIR10B18	CH024S346**	AFSH24-15.4		10.0	18.0	N/A	N/A	21.0"	15 3/8"	59**	49**
AFAIR12B18	CH024S346**	AFSH24-15.4		12.0	18.0	N/A	N/A	21.0"	15 3/8"	59**	53**
AFHEAT10B18	CH024S346**	AFSH24-15.4		10.0	18.0	17.6	6.8	21.0"	15 3/8"	59**	49**
AFAIR12B24	CH024S346**	AFSH24-15.4		12.0	23.6	N/A	N/A	21.0"	15 3/8"	59**	61**
AFAIR10B24-A	CH024S346	AFSH24-15.4		10.0	24.0	N/A	N/A	21.0"	15 3/8"	59	59
AFHEAT10B24	CH024S346	AFSH24-15.4		10.0	24.0	22.8	6.8	21.0"	15 3/8"	59	59
AFHEAT12B18	CH024S346+TXV**	AFSH24-15.4+TXV		12.0	17.4	17.0	7.2	21.0"	15 3/8"	59**	TXV2-A**
AFHEAT12B24	CH024S346+TXV**	AFSH24-15.4+TXV		12.0	22.8	22.8	7.5	21.0"	15 3/8"	59**	TXV2-A**
AFAIR12B30-A	CH036S566**	AFSH36-18.4		12.0	29.0	N/A	N/A	21.0"	18 3/8"	71**	68**
AFAIR10B30-A	CH036S566**	AFSH36-18.4		10.0	29.4	N/A	N/A	21.0"	18 3/8"	71**	63**
AFHEAT10B30	CH036S566**	AFSH36-18.4		10.0	30.0	29.0	6.8	21.0"	18 3/8"	71**	63**
AFAIR10B36-A	CH036S566	AFSH36-18.4		10.0	35.0	N/A	N/A	21.0"	18 3/8"	71	71
AFHEAT12B30	CH036S566+TXV**	AFSH36-18.4+TXV		12.0	29.2	29.0	7.5	21.0"	18 3/8"	71**	TXV2-A**
AFAIR12B36	CH036S566+TXV**	AFSH36-18.4+TXV		12.0	33.0	N/A	N/A	21.0"	18 3/8"	71**	TXV2-B**
AFHEAT10B36	CH048SA66**	AFSH48-28.1		10.0	34.4	34.4	6.8	21.0"	28 1/8"	82**	71**
AFAIR10B42	CH048SA66**	AFSH48-28.1		10.0	40.0	N/A	N/A	21.0"	28 1/8"	82**	76**
AFHEAT10B42	CH048SA66**	AFSH48-28.1		10.0	40.5	40.5	6.8	21.0"	28 1/8"	82**	76**
AFAIR10B48	CH048SA66	AFSH48-28.1		10.0	45.5	N/A	N/A	21.0"	28 1/8"	82	82
AFHEAT12B36	CH048SA66+TXV**	AFSH48-28.1+TXV		12.0	35.2	34.6	7.5	21.0"	28 1/8"	82**	TXV2-B**
AFAIR12B42	CH048SA66+TXV**	AFSH48-28.1+TXV		12.0	40.0	N/A	N/A	21.0"	28 1/8"	82**	TXV2-B**
AFHEAT12B42	CH048SA66+TXV**	AFSH48-28.1+TXV		12.0	42.0	41.5	7.5	21.0"	28 1/8"	82**	TXV2-B**
AFAIR12B48	CH048SA66+TXV**	AFSH48-28.1+TXV		12.0	47.0	N/A	N/A	21.0"	28 1/8"	82**	TXV2-B**
AFHEAT10B48	CH061SB97**	AFSH61-30.1		10.0	45.5	47.0	7.0	21.0"	30 3/8"	90**	82**
AFAIR10B60	CH061SB97	AFSH61-30.1		10.0	56.5	N/A	N/A	21.0"	30 3/8"	90	90
AFHEAT10B60	CH061SB97	AFSH61-30.1		10.0	57.0	58.5	7.0	21.0"	30 3/8"	90	90
AFHEAT12B48	CH061SB97+TXV**	AFSH61-30.1+TXV		12.0	47.0	48.0	8.0	21.0"	30 3/8"	90**	TXV2-B**
AFHEAT12B60	CH061SB97+TXV**	AFSH61-30.1+TXV		12.0	57.0	59.0	8.0	21.0"	30 3/8"	90**	TXV2-B**
AFAIR12B60	CH061SB97+TXV**	AFSH61-30.1+TXV		12.0	58.0	N/A	N/A	21.0"	30 3/8"	90**	TXV2-B**

** = 10.0 SEER UNITS REQUIRE A PISTON CHANGE TO MATCH OUTDOOR UNIT TONNAGE AND 11.0 SEER AND ABOVE UNITS ALL REQUIRE A PISTON CHANGE PER PISTON CHART (OR SEE REQUIRED PISTON ABOVE) IF NO TXV KIT IS SHOWN AS REQUIRED.

NOTE (1): IF A TXV IS SHOWN AS REQUIRED, IT IS INCLUDED IN THE PRICE AS FACTORY INSTALLED. CURRENT DELIVERY IS 3-4 WEEKS AFTER FINAL RELEASE WITH COMPLETE INFORMATION